AIR FITTINGS and ACCESSORIES

"AIR CHIEF" INDUSTRIAL QUICK-CONNECT FITTINGS

INDUSTRIAL INTERCHANGE

"Air Chief" Industrial Quick-Connect Fittings are of the popular Industrial Interchange design and will interchange with many other makes. Rated 300 PSI. Interchanges with MIL Spec. C-4109. Temp. range -40° to 250°F.

SEMI-AUTOMATIC - PULL SLEEVE TO CONNECT

COUPLERS SHUT-OFF WHEN DISCONNECTED

FOR AIR SERVICE ONLY

1/4" Plugs		Duroh	1/4" Couplers		Dort #	Dka Otv
Flow Rating: (steel)	Size Part #	Pkg Qty	(brass)	Size	Part # MALE N	Pkg Qty
37 CFM at 100 PSI	1/8" DCP2101	20	· · · ·			
	1/4" DCP21	20	and the second second	1/8" 1/4"	DC2101 DC21	10 10
	3/8" DCP2103	20		3/8"	DC2103	10
	FEMALE NPT			FEMALE NPT		
	1/8" DCP2021	20		1/8"	DC2021	10
	1/4" DCP20	20	0m 3 mm	1/4"	DC20	10
	3/8" DCP2023	20		3/8"	DC2023	10
	HOSE S	HANK			HOSE SH	IANK
Autor Autor	1/4" DCP2142	20		1/4"	DC2042	10
	5/16" DCP2143 3/8" DCP2144	20 20		5/16"	DC2043 DC2044	10 10
				3/8"	PUSH-ON HO	
	PUSH-ON HC		Too I Mental American			
	1/4" DCP2142L 3/8" DCP2144L	25		1/4" 3/8"	DC2042L DC2044L	25 25
	3/8" DCP2144L	25		3/8	DC2044L	25
		10				-
3/8" Plugs	Size Part #	Pkg Qty	3/8" Couplers	Size	Part #	Pkg Qty
Flow Rating: (steel) 70 CFM at 100 PSI	MALE	NPT	(steel)		MALEN	
70 CFM at 100 FSI	1/4" DCP2502	10	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1/4"	DC2502 DC25	10
Same and the same	3/8" DCP25 1/2" DCP2504	10	et i terrefer tur	3/8" 1/2"	DC25 DC2504	10 10
	FEMALE NPT			FEMALE NPT		
	1/4" DCP2622	10		1/4"	DC2622	10
	3/8" DCP2622	10		3/8"	DC26	10
	1/2" DCP2624	10		1/2"	DC2624	10
	HOSE SHANK			HOSE SHANK		
	1/4" DCP2542	10		1/4"	DC2642	10
	3/8" DCP2544	10		3/8"	DC2644	10
	1/2" DCP2545	10		1/2"	DC2645	10
200	PUSH-ON HOSE BARB			PUSH-ON HOSE BA		SE BARB
	1/4" DCP2542L	25		1/4"	DC2642L	25
	3/8" DCP2544L	25	ATT SHE	3/8"	DC2644L	25
				·		
1/2" Plugs	Size Part #	Pkg Qty	1/2" Couplers	Size	Part #	Pkg Qty
Flow Rating: (steel) 150 CFM at 100 PSI	MALE	MALE NPT (steel)		MALE NPT		
	3/8" DCP1703	10		3/8"	DC903	10
	1/2" DCP17	10	and the second sec	1/2"	DC9 DC906	10 10
	3/4" DCP1706			3/4"		
	FEMALE NPT					
	3/8" DCP1823 1/2" DCP18	10 10	the second second second	3/8" 1/2"	DC1023 DC10	10
	3/4" DCP1826	10	A CONTRACTOR OF THE OWNER	3/4"	DC1026	10
	HOSE SHANK			HOSE SHANK		
	3/8" DCP1744	10		3/8"	DC1044	10
	1/2" DCP1745	10		1/2"	DC1044 DC1045	10
Standing Address with support limited	3/4" DCP1746	10	and an and a second sec	3/4"	DC1046	10